



**GALAXY
EARTHMOVER**

TRA: **E-3/L-3**
Speed Rating: **A2**



CUT
RESISTANT
COMPOUND

LDSR 300 is specially constructed for wheel loaders operating in the toughest environments. Transportation of heavy load demands excellent stability and robustness. Sturdy radial construction coupled with strong sidewall protector provides LDSR 300 superior strength and endurance to withstand challenging terrains. Premium tread compounds provide excellent protection against lug-tearing and chunking, helping the machine to perform efficiently without any downtime. "S-shaped" tread pattern with stepped lugs ensure optimal traction and enhanced self-cleaning assuring high productivity.

EARTHMOVER - 17.5R25

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
		SW mm	OD mm					Speed									
								Load capacity for Loader Application									
								Static kmph	Creep kmph	5 kmph	10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	40 kmph	
17.5R25	14.00/1.5	445	1350	623	4009	182A2	6.5	13600	11050	9690	8500	7395	7140	6800	6545	5950	

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load											
		SW mm	OD mm					Speed											
								Load capacity for Earthmover application kg (lbs)											
								15 kmph	20 kmph	25 kmph	30 kmph	35 kmph	40 kmph	45 kmph	50 kmph	55 kmph	60 kmph	65 kmph	
17.5R25	14.00/1.5	445	1350	623	4009	167B	5.25	6100	6000	5900	5800	5700	5600	5600	5450	5300	5100	4800	

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer

