



**GALAXY
EARTHMOVER**

TRA: **E-3/L-3**
Speed Rating: **A2**



CUT
RESISTANT
COMPOUND

LDSR 300 is specially constructed for wheel loaders operating in the toughest environments. Transportation of heavy load demands excellent stability and robustness. Sturdy radial construction coupled with strong sidewall protector provides LDSR 300 superior strength and endurance to withstand challenging terrains. Premium tread compounds provide excellent protection against lug-tearing and chunking, helping the machine to perform efficiently without any downtime. "S-shaped" tread pattern with stepped lugs ensure optimal traction and enhanced self-cleaning assuring high productivity.

EARTHMOVER - 23.5R25

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
		SW mm	OD mm					Speed									
								Load capacity for Loader Application									
								Static kmph	Creep kmph	5 kmph	10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	40 kmph	
23.5R25	19.50/2.5	606	1615	717	4721	201A2	6.5	23200	18850	16550	14500	12600	12200	11600	11165	10150	

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load											
		SW mm	OD mm					Speed											
								Load capacity for Earthmover application kg (lbs)											
								15 kmph	20 kmph	25 kmph	30 kmph	35 kmph	40 kmph	45 kmph	50 kmph	55 kmph	60 kmph	65 kmph	
23.5R25	19.50/2.5	606	1615	717	4721	185B	5.25	10400	10200	10000	9800	9600	9500	9400	9250	9100	8700	8100	

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer

