



**GALAXY
EARTHMOVER**

TRA: **E-4/L-4**
Speed Rating: **A6**

HTSR 400 is specially built for dump trucks that face extreme environments while hauling heavy loads. High tread depth ensures consistent traction and greater cut resistance making it the more productive choice. The presence of special compound ensures minimum heat build-up while performing longer runs. Superior cut & chip protection with optimized belt design provides excellent durability resulting in reduced downtime.

RADIAL EARTH MOVER - 23.5R25

| Size | Rim | Unloaded Dimension | | Loaded Static radius mm | Rolling Circumference mm | Load Index PR Symbols | Inflation Pressure bar | Recommended Load | | | | | | | | | | |
|---------|-----------|--------------------|-------|-------------------------|--------------------------|-----------------------|------------------------|--|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| | | SW mm | OD mm | | | | | Speed | | | | | | | | | | |
| | | | | | | | | Load capacity for construction / waste management application on ADT (lbs) | | | | | | | | | | |
| | | | | | | | | 15 kmph | 20 kmph | 25 kmph | 30 kmph | 35 kmph | 40 kmph | 45 kmph | 50 kmph | 55 kmph | 60 kmph | 65 kmph |
| 23.5R25 | 19.50/2.5 | 608 | 1635 | 737 | 4735 | 185B | 5.25 | 10400 | 10200 | 10000 | 9800 | 9600 | 9500 | 9400 | 9250 | 9100 | 8700 | 8100 |

| Size | Rim | Unloaded Dimension | | Loaded Static radius mm | Rolling Circumference mm | Load Index PR Symbols | Inflation Pressure bar | Recommended Load | | | | | | | | | |
|---------|-----------|--------------------|-------|-------------------------|--------------------------|-----------------------|------------------------|---|------------|--------|---------|---------|---------|---------|---------|---------|--|
| | | SW mm | OD mm | | | | | Speed | | | | | | | | | |
| | | | | | | | | Load capacity for Loader application kg (lbs) | | | | | | | | | |
| | | | | | | | | Static kmph | Creep kmph | 5 kmph | 10 kmph | 15 kmph | 20 kmph | 25 kmph | 30 kmph | 40 kmph | |
| 23.5R25 | 19.50/2.5 | 608 | 1635 | 737 | 4735 | 201A2 | 6.5 | 23200 | 18850 | 16550 | 14500 | 12600 | 12200 | 11600 | 11165 | 10150 | |

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer

