



**GALAXY
EARTHMOVER**

TRA: **E-3**
Speed Rating: **A2**



CUT & CHIP
RESISTANT
COMPOUND

S-300 E-3/L-3 is the latest addition to Galaxy 's range of construction and mining tires. It is designed keeping in mind the versatility of the terrains on which these machines ply ranging from soft muddy soil to gravelly rocky terrain. The advanced S pattern promises exceptional traction, excellent stability and durability which ensures maximum productivity.

Bias Earthmover - 23.5-25

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load	
		SW mm	OD mm					Speed	
								Recommended Load Capacity (For Loader)	Recommended Load Capacity (For Transport)
		10 kmph	50 kmph						
23.5-25	19.50"x25"	623	1634	730	4840	24PR	3.5	NA	8000
							4.75	12500	NA

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load	
		SW mm	OD mm					Speed	
								Recommended Load Capacity (For Loader)	Recommended Load Capacity (For Transport)
		Max Load capacity	Max Load capacity						
		10 kmph	50 kmph						
23.5-25	19.50x25	623	1634	730	4840	20PR	3	NA	7300
							3.75	10900	NA

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer

