



**GALAXY
EARTHMOVER**

TRA: **E-3**
Speed Rating: **A2**



CUT & CHIP
RESISTANT
COMPOUND

S-300 E-3/L-3 is the latest addition to Galaxy 's range of construction and mining tires. It is designed keeping in mind the versatility of the terrains on which these machines ply ranging from soft muddy soil to gravelly rocky terrain. The advanced S pattern promises exceptional traction, excellent stability and durability which ensures maximum productivity.

Bias Earthmover - 20.5-25


Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load			
								Speed		Recommended Load Capacity (For Loader)	Recommended Load Capacity (For Transport)
		Max Load capacity						10 kmph	50 kmph		
		SW mm	OD mm					Max Load capacity		10 kmph	50 kmph
		20.5-25	17.00" x 25"					521	1493	650	4329
4.5	9500			NA							

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load			
								Speed		Recommended Load Capacity (For Loader)	Recommended Load Capacity (For Transport)
		Max Load capacity						10 kmph	50 kmph		
		SW mm	OD mm					Max Load capacity		10 kmph	50 kmph
		20.5-25	17.00" x 25"					521	1493	650	4329
3.5	8250			NA							

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer



Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load	
								Speed	
		Max Load capacity						Max Load capacity	
		SW mm	OD mm					10 kmph	50 kmph
		20.5-25	17.00x25					521	1493
5.25	10300			NA					

For ATC Tires Pvt Limited

Dan Steltmann
Chief Technology Officer