



**GALAXY  
EARTHMOVER**

TRA: **E-4/L-4**  
Speed Rating: **A6**

HTSR 400 is specially built for dump trucks that face extreme environments while hauling heavy loads. High tread depth ensures consistent traction and greater cut resistance making it the more productive choice. The presence of special compound ensures minimum heat build-up while performing longer runs. Superior cut & chip protection with optimized belt design provides excellent durability resulting in reduced downtime.

**RADIAL EARTH MOVER - 29.5R25**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load										
								Speed										
		Load capacity for construction / waste management application on ADT kg (lbs)																
		SW mm	OD mm					15 kmph	20 kmph	25 kmph	30 kmph	35 kmph	40 kmph	45 kmph	50 kmph	55 kmph	60 kmph	65 kmph
29.5R25	25.00/3.5	760	1890	852	5550	200B	5.25	15700	15400	15100	14800	14600	14400	14300	14000	13700	13200	12300

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
								Speed									
		Load capacity for Loader application kg (lbs)															
		SW mm	OD mm					Static kmph	Creep kmph	5 kmph	10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	40 kmph	
29.5R25	25.00/3.5	760	1890	852	5550	216A2	6.5	35840	29120	25540	22400	19500	18820	17920	17250	15680	

For ATC Tires Pvt Limited



Dan Steltmann  
Chief Technology Officer

