



**GALAXY
EARTHMOVER**

TRA: **E-3**
Speed Rating: **A2**



CUT & CHIP
RESISTANT
COMPOUND

S-300 E-3/L-3 is the latest addition to Galaxy 's range of construction and mining tires. It is designed keeping in mind the versatility of the terrains on which these machines ply ranging from soft muddy soil to gravelly rocky terrain. The advanced S pattern promises exceptional traction, excellent stability and durability which ensures maximum productivity.

Bias Earthmover - 14.00-24

| Size | Rim | Unloaded Dimension | | Loaded Static radius mm | Rolling Circumference mm | Load Index PR Symbols | Inflation Pressure bar | Recommended Load | |
|----------|------------|--------------------|-------|-------------------------|--------------------------|-----------------------|------------------------|------------------|---------|
| | | | | | | | | Speed | |
| | | Max Load capacity | | | | | | 50 kmph | 10 kmph |
| | | SW mm | OD mm | | | | | | |
| 14.00-24 | 10.00"x24" | 375 | 1348 | 616 | 4060 | 24PR | 5.75 | 5150 | NA |
| | | | | | | | 8.5 | NA | 9500 |

| Size | Rim | Unloaded Dimension | | Loaded Static radius mm | Rolling Circumference mm | Load Index PR Symbols | Inflation Pressure bar | Recommended Load |
|----------|---------|--|------|-------------------------|--------------------------|-----------------------|------------------------|------------------|
| | | | | | | | | Speed |
| | | Recommended Load Capacity (For Grader) | | | | | | |
| | | 40 kmph | | | | | | |
| 14.00-24 | 10"x24" | 375 | 1368 | 616 | 4060 | 16PR | 3.5 | 3650 |

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer

