



**GALAXY  
EARTHMOVER**

TRA: **E-3/L-3**  
Speed Rating: **A2**



CUT & CHIP  
RESISTANT  
COMPOUND

S-300 E-3/L-3 is the latest addition to Galaxy 's range of construction and mining tires. It is designed keeping in mind the versatility of the terrains on which these machines ply ranging from soft muddy soil to gravelly rocky terrain. The advanced S pattern promises exceptional traction, excellent stability and durability which ensures maximum productivity.

**Bias Earthmover - 26.5-25**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load	
		SW mm	OD mm					Speed	
								Recommended Load Capacity (For Loader)	Recommended Load Capacity (For Transport)
26.5-25	22x25	673	1740	770	5173	32PR	4.25	NA	11200
							5.5	17000	NA

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load	
		SW mm	OD mm					Speed	
								Recommended Load Capacity (For Loader)	Recommended Load Capacity (For Transport)
26.5-25	22x25	673	1740	770	5173	28PR	3.5	NA	10000
							4.75	15500	NA

For ATC Tires Pvt Limited



Dan Steltmann  
Chief Technology Officer

