



**GALAXY  
EARTHMOVER**

TRA: **E-3/L-3**  
Speed Rating: **A2**



CUT  
RESISTANT  
COMPOUND

LDSR 300 is specially constructed for wheel loaders operating in the toughest environments. Transportation of heavy load demands excellent stability and robustness. Sturdy radial construction coupled with strong sidewall protector provides LDSR 300 superior strength and endurance to withstand challenging terrains. Premium tread compounds provide excellent protection against lug-tearing and chunking, helping the machine to perform efficiently without any downtime. "S-shaped" tread pattern with stepped lugs ensure optimal traction and enhanced self-cleaning assuring high productivity.

**EARTHMOVER - 29.5R25**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
		SW mm	OD mm					Speed									
								Load capacity for Loader application kg (lbs)									
								Static kmph	Creep kmph	5 kmph	10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	40 kmph	
29.5R25	25.00/3.5	756	1862	821	5599	216A2	6.5	35840	29120	25540	22400	19500	18820	17920	17250	15680	

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load											
		SW mm	OD mm					Speed											
								Load capacity for Earthmover application kg (lbs)											
								15 kmph	20 kmph	25 kmph	30 kmph	35 kmph	40 kmph	45 kmph	50 kmph	55 kmph	60 kmph	65 kmph	
29.5R25	25.00/3.5	756	1862	821	5599	200B	5.25	15700	15400	15100	14800	14600	14400	14300	14000	13700	13200	12300	

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

For ATC Tires Pvt Limited



Dan Steltmann  
Chief Technology Officer

