



**GALAXY  
EARTHMOVER**

TRA: **E-3**  
Speed Rating: **A2**



CUT & CHIP  
RESISTANT  
COMPOUND

S-300 E-3/L-3 is the latest addition to Galaxy 's range of construction and mining tires. It is designed keeping in mind the versatility of the terrains on which these machines ply ranging from soft muddy soil to gravelly rocky terrain. The advanced S pattern promises exceptional traction, excellent stability and durability which ensures maximum productivity.

**Bias Earthmover - 17.5-25**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load	
								Speed	
		Max Load capacity						10 kmph	50 kmph
		SW mm	OD mm						
17.5-25	14.00"x25"	445	1348	610	4030	20PR	4	NA	5000
							5.75	8250	NA

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load	
								Speed	
		Max Load capacity						10 kmph	50 kmph
		SW mm	OD mm						
17.5-25	14.00x25	445	1348	610	4030	16PR	3	NA	4250
							4.75	7300	NA

For ATC Tires Pvt Limited



Dan Steltmann  
Chief Technology Officer

