



**GALAXY
EARTHMOVER**

TRA: **E-4/L-4**
Speed Rating: **A6**

HTSR 400 is specially built for dump trucks that face extreme environments while hauling heavy loads. High tread depth ensures consistent traction and greater cut resistance making it the more productive choice. The presence of special compound ensures minimum heat build-up while performing longer runs. Superior cut & chip protection with optimized belt design provides excellent durability resulting in reduced downtime.

RADIAL EARTH MOVER - 26.5R25

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load										
		SW mm	OD mm					Speed										
								Load capacity for construction / waste management application on ADT kg (lbs)										
								15 kmph	20 kmph	25 kmph	30 kmph	35 kmph	40 kmph	45 kmph	50 kmph	55 kmph	60 kmph	65 kmph
26.5R25	22.00/3.0	674	1750	794	5250	193B	5.25	12900	12700	12400	12200	12000	11800	11700	11500	11300	10800	10100

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
		SW mm	OD mm					Speed									
								Load capacity for Loader application kg (lbs)									
								Static kmph	Creep kmph	5 kmph	10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	40 kmph	
26.5R25	22.00/3.0	674	1750	794	5250	209A2	6.5	29600	24050	21100	18500	16100	15550	14800	14250	12950	

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer

